# **USER'S GUIDE ANALOG**

## CASIO

#### To set time

- 1) Pull the crown out when the second hand at 12 o'clock position and the second hand stops.
- 2) Set the hands by turning the crown.
- 3) In accordance with a time signal, push the crown in.



#### For watch with a date display

- 1) Pull the crown out to the second click when the second hand is at the 12 o'clock position and the second hand stops.
- 2) Turn the hands clockwise and put the watch four or five minutes forward. Then back them out
- 3) In accordance with a time signal, push the crown in.

#### To Set Date

- 1) Pull the crown out to the first click.
- 2) Set the day by turning the crown clockwise.
- 3) Push the crown in to the nomal position.





The configuration of your watch may differ somewhat from that shown in the illustration

#### For watch with a screwlock crown

- 1) Pull the crown out when the second click when the second hand is at the 12 o'clock position and the second hand stops.
- 2) Turn the hands clockwise and put the watch four or five minutes forward. Then back them out .
- 3) Push the crown in to the normal position on a time signal.

#### To Set Day-date

- 1) Pull the crown out to the first click.
- 2) Set the hands by turning the crown clockwise. Set the date by turning the crown counterclockwise. Check whether the day is English or Spanish.
- 3) Push the crown in to the nomal position.

Note: Avoid setting the day-date between 10:00 p.m. and 6:30 a.m. (the day-date display may not change in the following day).



(Setting day-date) Second click

The configuration of your watch may differ somewhat from that shown in the illustration


## [Day display]

| [Day alopiay] |         |
|---------------|---------|
| English       | Spanish |
| SUN           | DOM     |
| MON           | LUN     |
| TUE           | MAR     |
| WED           | MIE     |
| THU           | JUE     |
| FRI           | VIE     |
| SAT           | SAB     |
|               |         |

### For watch with a backlight

#### About the backlight

- Hold down (i) to illuminate the face of the watch.
- With Modules 1319 and 2312, pressing (L) illuminates the display for about two or three seconds.
- With Modules 2342 and 2343, pressing (L) illuminates the display for about one second.
- The backlight of this watch employs an electroluminescent (EL) light, which loses its illuminating power after very long term use.
- Frequent use of the backlight shortens the battery life.
- Leaving the backlight on for a long time or turning on the backlight while battery power is low can cause the hands of the watch to stop momentarily.



#### For watch with the elapsed time bezel

Rotate the elapsed time bezel to align the \partial mark with the

After certain amount of time elapsed, read the graduation on the elapsed time bezel which the minute hand points to. The elapsed time is indicated.



### • For watch with a screwlock crown

#### About the screwlock crown

- Some water resistant models are equipped with a screwlock
- With such models, you must unscrew the crown in the direction noted in the illustration to loosen it before you can pull it out. Do not pull too forcibly on such crowns.
- Also note that such watches are not water resistant while their. crowns are loosened. Be sure to screw the crowns back in as far as they will go after making any setting.

