

CT-S1 Casiotone

Quick Start Guide

Preparing a Power Supply

Using the AC Adaptor

illustration.

For more detailed information about the product and its operation, visit the CASIO website. Available Information: User's Guide, etc. https://support.casio.com/global/en/emi/manual/CT-S1/



After reading this document, keep it in a safe place along with the warranty certificate. Be sure to read the

Included Accessories

READ THIS! Sheet

• Other (Warranty, etc.)

• Strap Lock (enclosed with music stand)

Items included as accessories are subject to change

Music Stand

Leaflets

without notice.

"Safety Precautions" in the separate "READ THIS!" sheet, and use the product correctly.

CASIO®

ΕN

Practicing with the Metronome



2 Specify a beat value.






(3) Specify the tempo.













Preparation




for this Digital Keyboard.


(1) Connect the AC adaptor as shown in the right

(2) Load six AA-size batteries.



(4) Specify the battery type. See "Specifying the Battery Type" on the reverse side of this sheet





Useful Functions

For details about operations, refer to the User's Guide on the CASIO Website.

My Setup

Save the current setup (tone, etc.) for later recall.

Reverb Output sounds using room, hall, and other acoustic effects. Octave Shift Raise or lower the pitch of the keyboard in octave units.


Transpose Raise or lower the overall pitch in semitone steps.


While holding down...

TONE VARIATION


+














(

(and

WIWIW

Product Specifications

- Model: CT-S1BK/CT-S1WE/CT-S1RD Keyboard: 61 keys Touch Response: 3 levels, Off Maximum Polyphony: 64 notes Tone Functions: 61 preset tones; Main tone buttons; Layer; Sustain; Tone Memory Effects: Reverb (24 types, Tone, Off); Chorus; Delay; DSP Metronome: Bell sound off, 1 to 16 beats; Tempo Range: 20 to 255 Demo Function: 1 demo song; 10 piano demo songs Function Volume Adjustment: Metronome MIDI Recorder: Real-time Recording, Playback; Number of Songs: 1; Capacity: Approximately 40,000 notes
- Other Functions: Transpose (±1 octave, -12 to 0 to +12 semitones); Octave Shift (±3 octaves); Tuning (A4 = 415.5 to 465.9 Hz; Default = 440.0 Hz); Scales (17 preset scales)
- APP Function: iOS, Android supported (connected via the USB terminal) MIDI: 16-channel multi-timbre receive
- jack: Stereo mini jack (3.5mm) (Input impedance: $10k\Omega$, Input sensitivity: 200mV); (6.3mm) (pedal sustain, sostenuto, soft, metronome)


Power Jack: 9.5VDC

- Power Supply: 2-way power supply; Auto Power Off (30-minute trigger time; Can be disabled)
- Batteries: 6 AA-size alkaline batteries or AA-size rechargeable nickel metal hydride batteries; Approximately 3 hours (alkaline batteries) or approximately 3 hours (nickel metal hydride batteries) continuous operation* * Measured values while using eneloop batteries.
- eneloop is a trademark of Panasonic Corporation.
- Actual continuous operation time may be shorter due to battery type, performance type, and usage environment.
- sudden loss of power.
- AC Adaptor: AD-E95100L (JEITA Standard, with unified polarity plug) Speakers: 13 cm × 6 cm (oval) × 2 (Output: 2.5W+2.5W)

Power consumption: 9.5V---7.5W Dimensions: 93.0(W) × 25.8(D) × 8.3(H) cm (36 5/8 × 10 3/16 × 3 1/4 inch)

Weight: Approximately 4.5 kg (9.9 lbs) (Excluding batteries)

Specifications and designs are subject to change without notice



Press again. (To execute)

This causes a re-start

- Any reproduction of the contents of this manual, either in part or its entirety, is prohibited. Except for your own, personal use, any other use of the contents of this manual without the consent of CASIO is prohibited under copyright laws.
- IN NO EVENT SHALL CASIO BE LIABLE FOR ANY DAMAGES WHATSOEVER (INCLUDING, WITHOUT LIMITATION, DAMAGES FOR LOSS OF PROFITS, BUSINESS INTERRUPTION, LOSS OF INFORMATION) ARISING OUT OF THE USE OF OR INABILITY TO USE THIS MANUAL OR PRODUCT. EVEN IF CASIO HAS BEEN ADVISED OF THE POSSIBILITY OF SUCH DAMAGES.
- The contents of this manual are subject to change without notice.
- Company and product names used in this manual may be registered trademarks of others.

Declaration of Conformity

Model Number: CT-S1 Trade Name: CASIO COMPUTER CO., LTD.

Responsible party: CASIO AMERICA, INC.

Address: 570 MT. PLEASANT AVENUE, DOVER, NEW JERSEY 07801 Telephone number: 973-361-5400

This device complies with Part 15 of the FCC Rules, Operation is subject to the following two conditions:

(1) This device may not cause harmful interference, and (2) this device must accept any interference received, including interference that may cause undesired operation.

A labels rating is affixed to the bottom of the product.

Functions Not Covered in This Manual

These instructions provide general information about main functions. For more detailed information, refer to the "User's Guide".

https://support.casio.com/global/en/emi/manual/CT-S1/

The "User's Guide" includes information on the topics listed below.

- Saving a Setup (My Setup)
- Playing with Reverb
- Changing the Pitch in Octave Units (Octave Shift)
- Changing the Pitch in Semitone Units (Transpose)
- Playing with a More Expanded Sound (Surround)
- Changing the Scale (Scale Tuning)
- Other

CASIO COMPUTER CO., LTD. 6-2, Hon-machi 1-chome Shibuya-ku, Tokyo 151-8543, Japan

> C MA2011-A Printed in China © 2021 CASIO COMPUTER CO., LTD.

Input/Output Terminals: PHONES/OUTPUT jack: Stereo mini jack (3.5mm); AUDIO IN USB TO HOST port: micro B; USB TO DEVICE port: Type A; PEDAL jack: Standard jack

• Specifying the wrong battery type can cause incorrect display of the battery level and